

## Angel 1608 / 1902



### Technical Parameters:

Model	Angel 1608	Angel 1902
Print width	1600mm	1900mm
Printhead/Quantity	Dx8 / 2-3	
Max thickness	1.5mm-2.5mm Optional	
Precision	GEN5 (dpi):- 360, 540, 720, 1440	
Ink supply system	Automatic Ink supply	
Color	CMYK	
Ink	Water Based / Eco Solvent	
Speed	4 Pass:- 36m <sup>2</sup> /h-48m <sup>2</sup> /h & 6 Pass:- 24m <sup>2</sup> /h-36m <sup>2</sup> /h	
Print media	Banner,lightsheet,softmembrane, smalipox,wallpaper,leather,one way vison, PVCfilm and various types of indoor and outdoor material	
Dry System	Fan and infrared drying	
RIP software	Photoprint/Maintop (optional)	
Operating system	Window 7 32/64bit RAM ≥ 8GB	
Environment	Temperature 18 to 26°C , relative humidity 40% -70%	
File format	TIFF,JPEG,EPS,PDF	
Power supply	Most Power 5.8KW, AC, 50Hz/60Hz, 220V (±10%) > 15A	
Machine Size	(L*W*H) 2210mm*800mm*1340mm	(L*W*H) 2910mm*800mm*1340mm
Package Size	(L*W*H) 3100mm*900mm*760mm	(L*W*H) 3300mm*900mm*760mm